



Maintenance and Cleaning

ColourStar - Commercially Laundered Process

ColourStar is a rubber backed mat and can be commercially laundered.

- Flush for 2-3 minutes, medium water level, 49°C
 - Break 5-10 minutes, high water level, 49°C
 - Rinse 2 minutes, high water level, cold
 - Extract (low speed) 1-2 minutes
 - Shake out (rotate wheel at wash speed with drain open) 1-2 minutes
 - Extract (high speed max – 250 Gs) 3-5 minutes
 - Dry 5-10 minutes, 82°C basket temperature
 - Cool down 5 minutes
 - Lay mats flat following removal from washer or dryer. Allow to cool before rolling
-
- For heavy soil mats, increase temperature to max 60°C
 - Break shouldn't exceed pH of 9.5; use low pH non-ionic detergents
 - Do not over-dry mats
 - Basket temperature of dryer should not exceed 82°C
 - If mats are not dried, final rinse can be increased to 60°C. This will reduce moisture retention following extraction

[Product Name] regular maintenance

- Vacuum daily in high traffic areas. Vacuum weekly in lower-traffic applications.
- Clean with an extractor or hose off as necessary to remove heavy soil. Hang to dry.
- Mats should always be completely dry before they are placed back in service.

STORAGE AND HANDLING

- Roll the mat in a compact roll with pile facing out. Lay flat. Do not crush. Store in a moderate temperature and dry area. CAUTION: if the borders on matting become broken or curled, the mat should be removing from service until the tripping hazard can be corrected
- Matting must never be stored on-end. This will cause the edges to curl and will void warranty. For proper storage, roll mat with top surface to the outside and lay flat in a protected area. Do not stack any materials or other mat on top of a stored mat.