



DATA SHEET

Manufacturer/ Distributor	Advance Flooring Systems Ltd
Trade Names	AKOPlus Safety mat
Product Description	PVC foam-coated glass fibre yarn with a PVC granulate surface.
Particular Benefit	Long lasting highly slip resistant matting, suitable for use in slippery or icy environments.
Area of Application	Ideal for use in both interior and exterior locations needing anti-slip and antifatigue matting. As anti-slip sound absorbent matting in accessways of factories, offices, homes, schools, on paths, passages, ramps and stairs.
Composition	PES/ Glass fibre yarn coated on both sides with proprietary PVC foam having PVC granulate bonded on top surface of mat. Weight 2000gsm.
Dimensions	Roll Width: 900mm, 1200mm, 1800mm Length: 10m Thickness: 6-7mm AKOPlus Safety mat can be cut to client specification without fraying.
Colour	Black
Manufacture	AKOPlus is manufactured in Germany by Kolckmann GmbH
UV Resistance	Classified as UV resistant, however some shade variation may become apparent in UV intense locations.

Data Sheet AKOPlus Safety Matting - 08/18



Moisture Behaviour	Water resistant – not affected by warm or cold conditions.
Safety	High slip resistant even in wet or icy conditions.
Installation	Mats are self-securing over 3sqm or can be secured with screws, washers, staples or carpet bars.
Cleaning and Maintenance	Easily cleaned with vacuum cleaner or pressure washer. Avoid high water pressure.
Guarantee	Guaranteed for 1 year against premature failure due to manufacturing defects.
Supply	Advance Flooring Systems Ltd has a national network of matting consultants and distributors. Please phone Advance for details of those in your area – toll free 0508 ADVANCE (0508 238 262).