## Data Sheet Treadman - 11/18



## **DATA SHEET**

Manufacturer/ Distributor Advance Flooring Company

131 Captain Springs Rd, Onehunga, Auckland

Ph 09-634 4455 or 0508 Advance (0508 238 262)

Trade Names Treadman

Product Description Rubber matting in sheet and roll form

Particular Benefit Anti-slip, impact resistant

Area of Application Treadman is suitable for gymnasiums, horse floats, animal comfort,

e.g. wintering barns, trucks.

Composition 100% natural rubber

Dimensions Sheets: 2000mm x 1000mm x 10mm

Rolls: 2000 x 20m x 10mm

Colour Sheets: Ribbed on side, hammered finish reverse side – black only

Rolls: Smooth on one side, hammered finish reverse side – black only

Static Anti-static

Fire resistance Does not ignite easily

Durability Heavy-duty



## Data Sheet Treadman - 11/18



Moisture Behaviour Nil, except to reduce anti-slip qualities.

Sound Absorption Good

Safety Excellent slip resistance when dry. Slip resistance is reduced when wet

although still better than many other surfaces

Installation Can be loose laid in most situations.

To glue down (for horse floats, etc.) the following procedure **must** be followed:

Subfloor must be free of wax, dust and grease, must be clean and free of

hydrostatic pressure.

Rubber matting must be wiped on the side to be glued with a solvent to remove traces of silicone. This side must then be primed with Bostick Boscosal "S" following manufacturer's instructions. Let primer dry. Glue down with a suitable adhesive (e.g. Roberts 600) following

manufacturer's instructions.

Cleaning/ Maintenance Water with mild detergent if required. Avoid strong detergents and chlorine.

Guarantee Guaranteed for 5 years against premature failure due to manufacturing

defects.

Supply Advance has a national network of consultants and distributors. Please view

our website at **www.advancefloors.co.nz** to locate your nearest stockist or phone toll free 0508 Advance (0508 238 262) New Zealand or 1800 51-52-53

Australia.

